



安腾彩钢
Anteng Caigang

20尺双翼折叠房技术参数表

Technical parameters of 20-foot double wing folding room

价格表
Price List

序号No.	种类Category	数量NUM	单价/Unit price/set	Total
20-foot double wing folding	6320*5800*H2480, Ordinary Windows, without floor leather	1	\$6000	Ordinary plastic steel doors and Windows
20-foot double wing folding	6320*5800*H2480, Aluminum alloy window with floor leather	1	\$6,500.00	High-grade broken bridge aluminum doors and Windows
40-foot double wing folding	6320*11600*H2480, Aluminum alloy window with floor leather	1	\$11,400.00	

exw TOTAL:



\$0.00



Production time - 25 days

技术参数表
Technical parameter table

基本特征 Basic characteristics	External dimension(mm)	6320*5800*H2480
	Folded state(mm)	6320*2200*H2480
	Gross mass (kg)	2800
	Top side beam	t2.5mmQ235B
	Bottom side beam	t2.5mmQ235B
	Top side beam	t2.5mmQ235B



框架结构 Frame structure	Side wall frame	t2.0mmQ235B	
	Second frame	t2.0mmQ235B	
	Angle hanger	t4mmQ235B	
	Folding hinge	13mm Galvanized hinge	
	Overall frame protection paint	Electrostatic spray/ Plain plastic powder	
	Middle cabinet top and bottom	80*100*2.5mm Square tube	
	Side cabinet top and bottom	40*60*2.0mm Square tube	
顶部 roof	External top plate	t0.5mm Galvanized plate	
	Internal ceiling	t0.35mm Model 831 ceiling panel	
墙板 wallboard	Middle top insulation	t50mmGlass Wool (Side top50-75mm EPS)	 
	Side wall, front and rear wall panels	t50mm EPS	
	Internal partition	t50mm EPS	
地板 floor	中间地板 Intermediate floor	Fireproof glass magnesium floor 15MM	 
	两边地板 Two-sided floor	Bamboo floorings 18MM	

地面装饰 Floor decoration	PVC floor leather 1.6mm	
电气系统 Electrical system	电器布线，严格按照防潮规范安装，所有电器产品都需符合CE认证。根据电路工程规范连接电路，室内：LED灯3个，五孔单开插座3个，十孔插座3个，空调插座3个，20A漏电保护器1个。 Electrical wiring is installed in strict accordance with moisture-proof specifications, and all electrical products must comply with CE certification. Connect the circuit according to the circuit engineering specification, indoor: 3 LED lights, 3 five-hole single socket, 3 10-hole socket, 3 air conditioning socket, 1 20A leakage protector. 电压220V,50HZ The voltage is 220V,50HZ	 
入 Entrance doors	铝合金防盗门970*1970 Aluminum alloy security door 970*1970	
窗户 Window	断桥铝双层玻璃920*920+(卫生间40*60)。 Broken bridge aluminum double glazing 920*920+(bathroom 40*60)	
卫生间 Toilet	(1400*1700)陶瓷马桶.洗手池.淋浴间.镜子.出水管。 (1400*1700) Ceramic toilet. Sink. Shower. Mirror. Outlet pipe	
橱柜 kitchen cabinet	L型橱柜L-kitchen cabinet	
质量保证 quality guarantee	One year warranty	

